



Quikcote Victoria Plaster Technology Pty Ltd ABN 76 078 391 545
26–30 Fleet Street Somerton, Victoria 3062
Factory 9303 7791 Fax 9303 7792
Email info@quikcote.com.au Web www.quikcote.com.au

Quikcote EPS Styrene Render is a high polymer cementitious based Acrylic Render.

Quikcote EPS Styrene Render has been manufactured to give extreme strength, durability and long term weather proofing.

Quikcote EPS Styrene Render can be used for polystyrene applications only, due to its bonding strength and flexibility.

Quikcote EPS Styrene Render is suitable for:

- Expanded Polystyrene only.

SURFACE PREPARATION

To ensure correct adhesion, surfaces must be suitably flat and clean ie: free of contaminants such as grease, waxes, paint and any oil based substances.

APPLICATION

Exterior: Quikcote EPS Render is used as base coat.

- Apply a bedding coat of Quikcote EPS Styrene Render, and then embed alkaline resistant mesh into the 1st coat while it is still wet, then let DRY.
- Apply 2nd coat of EPS Styrene Render finishing off with styrene or plastic float.
- Use Quikcote Colorcote or Quikcote Acrylic Texture as final finish or suitable product to achieve desired finish.

For **Styrene Application**, please contact Quikcote for more detailed information.

COVERAGE

On smooth surface : approx 5 - 10sq. metres.

TECHNICAL DATA

Specific Gravity: 1.86 kg/lt

Odor: Nil

Base: Cement

Surface Finish: Medium

Weather Resistance: High

PH: 11

Viscosity of Mix: (CPS) 95,000

GUARANTEE:

All products are guaranteed for seven years under *normal conditions. This product should be used in accordance with directions which are only a guide. Quikcote accepts no responsibility for inappropriate use or faulty workmanship. All mineral earth based aggregate /course filler based renders and textures will contain a low percentage of carbon and/or ferrous contaminants and can occasionally spot the surface. All care is taken in raw material selection to minimize such effects. Quikcote accepts no responsibility for this occasional occurrence.

IDENTIFICATION

Product Name: Quikcote EPS Styrene Render

UN Number: na

Poisons Schedule Number:na

PHYSICAL DESCRIPTION

Appearance: Off White

Vapor Pressure: na

Specific Gravity: 1.86 @ 25 Degrees Celsius

Flammability: na

Solubility: Water Soluble

HAZARDOUS INGREDIENTS

Sand >50%

Cement >30%

Proprietary additives (non hazardous) <20%

Remaining products are not deemed to be hazardous and are commercially confidential.

HEALTH HAZARD & FIRST AID INFO

- SKIN CONTACT:**

Prolonged exposure may cause skin irritation:
Wash off with water.

- EYE CONTACT:**

May cause pain: Irrigate with water for at least 15 min.

- IF SWALLOWED:**

Single dose oral toxicity is low BUT do not induce vomiting. DO call a doctor and transport to emergency facility for further instructions.

- IF INHALED:**

Prolonged inhalation may cause irritation:
Ensure adequate ventilation.

- ENSURE SAFETY GLASSES ARE WORN FOR EYE PROTECTION**

- GLOVES, BOOTS AND OVERALLS SHOULD BE WORN FOR PROLONGED CONTACT.**

SPILLS: SMALL SPILLS: SHOULD BE MOPPED UP OR SOAKED UP . LARGE SPILLS: SHOULD BE CONTAINED. AVIOD SPILLAGE INTO WATER SUPPLIES.

CLEAN UP

Warm water clean –up prior to drying.