



Quikcote Victoria Plaster Technology Pty Ltd ABN 76 078 391 545
26–30 Fleet Street Somerton, Victoria 3062
Factory 9303 7791 Fax 9303 7792
Email info@quikcote.com.au Web www.quikcote.com.au

Quikcote Membrane is high acrylic polymer paint, premixed and colored in a 15 litre pail.

Quikcote Membrane has been manufactured to give extreme strength, durability and long term weather proofing.

Quikcote Membrane is suitable for:

- All Masonary surfaces
- Rendered surfaces
- Cement sheet application eg:
- Blue board, C.S.R & Hardies
- Polystyrene Application (refer to Quikcote Styrene System)

SURFACE PREPARATION

To ensure correct adhesion, surfaces must be suitably flat and clean ie: free of contaminants such as grease, waxes, any oil based substances.

APPLICATION

Exterior: Quikcote Membrane is a two coat application it is used as applied finish or final coat over rendered and textured surfaces.

Applying Quikcote membrane should be done at temperatures of above 10°C and temperatures below 30°C.

1. Apply armororing first coat of Quikcote Membrane to entire surface of project, with either brush or roller.
2. Final coat to be applied on setting of first coat.

Note: Check the weather forecast. Do not apply membrane finishes on excessively cold or humid days, or when rain is anticipated within 8hours. Exposure to rain or overnight due may result in coating being damaged or removed.

- Do not thin

COVERAGE : approx. 20- 30 sq. metres.
Depending on surface.

TECHNICAL DATA

Specific Gravity: 1.86 kg/lit
Odor: Acrylic Paint
Surface Finish: Membrane
Weather Resistance: High
PH: 11
Viscosity of Mix: (CPS) 95,000

GUARANTEE:

All products are guaranteed for seven years under *normal conditions.

This product should be used in accordance with directions which are only a guide. Quikcote accepts no responsibility for inappropriate use or faulty workmanship. All mineral earth based aggregate /course filler based renders and textures will contain a low percentage of carbon and/or ferrous contaminants and can occasionally spot the surface. All care is taken in raw material selection to minimize such effects. Quikcote accepts no responsibility for this occasional occurrence.

IDENTIFICATION

Product Name: Quikcote Membrane.
UN Number: na
Poisons Schedule Number:na
Purpose: Surface Coating

PHYSICAL DESCRIPTION

Appearance: Any Colour
Vapor Pressure: na
Specific Gravity: 1.86 @ 25 Degrees Celsius
Flammability: na
Solubility: Water Soluble

HAZARDOUS INGREDIENTS

Marble >80%
Proprietary additives (non hazardous) <20%
Remaining products are not deemed to be hazardous and are commercially confidential.

HEALTH HAZARD & FIRST AID INFO

- **SKIN CONTACT:**

Prolonged exposure may cause skin irritation:
Wash off with water.

- **EYE CONTACT:**

May cause pain: Irrigate with water for at least 15 min.

- **IF SWALLOWED:**

Single dose oral toxicity is low BUT do not induce vomiting. DO call a doctor and transport to emergency facility for further instructions.

- **IF INHALED:**

Prolonged inhalation may cause irritation:
Ensure adequate ventilation.

- **ENSURE SAFETY GLASSES ARE WORN FOR EYE PROTECTION**

- **GLOVES, BOOTS AND OVERALLS SHOULD BE WORN FOR PROLONGED CONTACT.**

SPILLS: SMALL SPILLS: SHOULD BE MOPPED UP OR SOAKED UP . LARGE SPILLS: SHOULD BE CONTAINED. AVIOD SPILLAGE INTO WATER SUPPLIES.

CLEAN UP

Warm water clean –up prior to drying.