



Quikcote Victoria Plaster Technology Pty Ltd ABN 76 078 391 545  
26–30 Fleet Street Somerton, Victoria 3062  
Factory 9303 7791 Fax 9303 7792  
Email [info@quikcote.com.au](mailto:info@quikcote.com.au) Web [www.quikcote.com.au](http://www.quikcote.com.au)

**Quikcote Acrylic Dry Render- Grey, Course & Fine** is a cementitious based acrylic finish, providing a fine or course surface profile for long term weather proofing of exterior surfaces.

**Quikcote Acrylic Dry Render- Grey, Course & Fine** is manufactured using the highest quality products giving strength, durability, strength and long term resistance to weathering.

**Quikcote Acrylic Dry Render- Grey, Course & Fine** is a very workable product, with ease of application and finishing. It can be used not only for new surfaces but is ideal for resurfacing and rejuvenation of existing surfaces.

Quikcote Acrylic Dry Render is suitable for:

- Brick
- Concrete
- Aerated Blocks (AAC Blocks)
- Pre-cast panel
- Concrete Block & Bricks

#### **SURFACE PREPARATION**

To ensure correct adhesion, surfaces must be suitably flat and clean ie: free of contaminants such as grease, waxes, paint and any oil based substances.

#### **APPLICATION**

Apply with a flat trowel and finishing with a polystyrene float for correct seal prior to application of surfacing finishes. Or it can be further textured with a sponge float for a sand like finish prior to painting or desired look.

#### **COVERAGE**

5.0m<sup>2</sup> per bag depending on surface per 20kg bag

#### **TECHNICAL DATA**

Specific Gravity: 1.86 kg/lt  
Odor: Nil  
Base: Cement  
Surface Finish: Medium  
Weather Resistance: High  
PH: 11  
Viscosity of Mix: (CPS) 95,000

#### **GUARANTEE:**

All products are guaranteed for seven years under  
\*normal conditions.

This product should be used in accordance with directions which are only a guide. Quikcote accepts no responsibility for inappropriate use or faulty workmanship. All mineral earth based aggregate /course filler based renders and textures will contain a low percentage of carbon and/or ferrous contaminants and can occasionally spot the surface. All care is taken in raw material selection to minimize such effects. Quikcote accepts no responsibility for this occasional occurrence.

#### **IDENTIFICATION**

Product Name: Grey acrylic render course /fine  
UN Number: na  
Poisons Schedule Number:na  
Purpose: Surface Coating

#### **PHYSICAL DESCRIPTION**

Appearance: Grey  
Vapor Pressure: na  
Specific Gravity: 1.86 @ 25 Degrees Celsius  
Flammability: na  
Solubility: Water Soluble

#### **HAZARDOUS INGREDIENTS**

Sand >50%  
Cement >30%  
Proprietary additives (non hazardous) <20%

**Remaining products are not deemed to be hazardous and are commercially confidential.**

#### **HEALTH HAZARD & FIRST AID INFO**

##### • SKIN CONTACT:

Prolonged exposure may cause skin irritation:  
Wash off with water.

##### • EYE CONTACT:

May cause pain: Irrigate with water for at least 15 min.

##### • IF SWALLOWED:

Single dose oral toxicity is low BUT do not induce vomiting. DO call a doctor and transport to emergency facility for further instructions.

##### • IF INHALED:

Prolonged inhalation may cause irritation:  
Ensure adequate ventilation.

##### • ENSURE SAFETY GLASSES ARE WORN FOR EYE PROTECTION

##### • GLOVES, BOOTS AND OVERALLS SHOULD BE WORN FOR PROLONGED CONTACT.

**SPILLS: SMALL SPILLS: SHOULD BE MOPPED UP OR SOAKED UP . LARGE SPILLS: SHOULD BE CONTAINED. AVIOD SPILLAGE INTO WATER SUPPLIES.**

#### **CLEAN UP**

Warm water clean –up prior to drying.