



Quikcote Victoria Plaster Technology Pty Ltd ABN 76 078 391 545
26–30 Fleet Street Somerton, Victoria 3062
Factory 9303 7791 Fax 9303 7792
Email info@quikcote.com.au Web www.quikcote.com.au

Quikcote Dry Acrylic Render is a cementitious based acrylic finish, providing a fine surface profile for long term weather proofing of exterior surfaces.

Quikcote Dry Acrylic Render is manufactured using the highest quality products giving strength, durability and long term resistance to weathering.

Quikcote Dry Acrylic Render is very workable product, with ease of application and finishing. It can be used not only for new surfaces but is ideal for resurfacing and rejuvenation of existing surfaces.

Quikcote Dry Acrylic Render is suitable for:

- Brick
- Concrete
- Pre-cast panel
- Concrete Block & Bricks

SURFACE PREPARATION

To ensure correct adhesion, surfaces must be suitably flat and clean ie: free of contaminants such as grease, Waxes, paint and any oil based substances.

APPLICATION

Apply with a flat trowel and finish with a polystyrene float for correct seal prior to application of surfacing finishes. Or it can be further textured with a sponge float for a sand like finish prior to painting.

COVERAGE

5.0m² per bag depending on surface per 20kg bag

TECHNICAL DATA

Specific Gravity: 1.86 kg/lit
Odor: Nil
Base: Cement
Surface Finish: Medium
Weather Resistance: High
PH: 11
Viscosity of Mix: (CPS) 95,000

CLEAN UP

Warm water clean –up prior to drying.

GUARANTEE:

All products are guaranteed for seven years under *normal conditions.

This product should be used in accordance with directions which are only a guide. Quikcote accepts no responsibility for inappropriate use or faulty workmanship. All mineral earth based aggregate /course filler based renders and textures will contain a low percentage of carbon and/or ferrous contaminants and can occasionally spot the surface. All care is taken in raw material selection to minimize such effects. Quikcote accepts no responsibility for this occasional occurrence.

IDENTIFICATION

Product Name: Bag Mix Render
UN Number: na
Poisons Schedule Number:na
Purpose: Surface Coating

PHYSICAL DESCRIPTION

Appearance: Off White
Vapor Pressure: na
Specific Gravity: 1.86 @ 25 Degrees Celsius
Flammability: na
Solubility: Water Soluble

HAZARDOUS INGREDIENTS

Sand >50%
Cement >30%
Proprietary additives (non hazardous) <20%
Remaining products are not deemed to be hazardous and are commercially confidential.

HEALTH HAZARD & FIRST AID INFO

- **SKIN CONTACT:**
Prolonged exposure may cause skin irritation:
Wash off with water.
- **EYE CONTACT:**
May cause pain: Irrigate with water for at least 15 min.
- **IF SWALLOWED:**
Single dose oral toxicity is low BUT do not induce vomiting. DO call a doctor and transport to emergency facility for further instructions.
- **IF INHALED:**
Prolonged inhalation may cause irritation:
Ensure adequate ventilation.
- **ENSURE SAFETY GLASSES ARE WORN FOR EYE PROTECTION**
- **GLOVES, BOOTS AND OVERALLS SHOULD BE WORN FOR PROLONGED CONTACT.**
SPILLS: SMALL SPILLS: SHOULD BE MOPPED UP OR SOAKED UP . LARGE SPILLS: SHOULD BE CONTAINED. AVIOD SPILLAGE INTO WATER SUPPLIES.