



Quikcote Victoria Plaster Technology Pty Ltd ABN 76 078 391 545
26–30 Fleet Street Somerton, Victoria 3062
Factory 9303 7791 Fax 9303 7792
Email info@quikcote.com.au Web www.quikcote.com.au

Quikcote Hebel Render is a cementitious with an acrylic base enabling good adhesion and strength to bind to hebel substrates.

Quikcote Hebel Render is manufactured using the highest quality products giving strength, durability and long term resistance to weathering.

Quikcote Hebel Render is very workable product, with ease of application and finishing. It can be used not only for new surfaces but is ideal for resurfacing and rejuvenation of existing surfaces.

Quikcote Hebel Render is suitable for:

- Brick
- Concrete
- Aerated Blocks (AAC Blocks)
- Pre-cast panel
- Concrete Block & Bricks

SURFACE PREPARATION

To ensure correct adhesion, surfaces must be suitably flat and clean ie: free of contaminants such as grease, Waxes, paint and any oil based substances.

APPLICATION

Hebel Blocks

Apply with a flat trowel; putting on one thin coat 1mm-2mm thick. After 2-3 hours of initial set time, then apply 2nd coat. Finishing off with styrene float or appropriate tooling.

Hebel Panel

First use alkaline resistant mesh on hebel joints then using Quikcote Quikpatch as bonding render for joints on hebel panel. Once joints have dried. Apply Quikcote Hebel Render over entire surface. When dry, apply a second coat and finish off with styrene float. Surface when dry, is ready for one of Quikcote applied finishes.

COVERAGE

4-5.0m² per bag depending on surface per 20kg bag

TECHNICAL DATA

Specific Gravity: 1.86 kg/ltr

Odor: Nil

Base: Cement

Surface Finish: Medium

Weather Resistance: High

PH: 11

Viscosity of Mix: (CPS) 95,000

GUARANTEE:

All products are guaranteed for seven years under *normal conditions.

This product should be used in accordance with directions which are only a guide. Quikcote accepts no responsibility for inappropriate use or faulty workmanship. All mineral earth based aggregate /course filler based renders and textures will contain a low percentage of carbon and/or ferrous contaminants and can occasionally spot the surface. All care is taken in raw material selection to minimize such effects. Quikcote accepts no responsibility for this occasional occurrence.

IDENTIFICATION

Product Name: Hebel Render

UN Number: na

Poisons Schedule Number: na

Purpose: Surface Coating

PHYSICAL DESCRIPTION

Appearance: Off White

Vapor Pressure: na

Specific Gravity: 1.86 @ 25 Degrees Celsius

Flammability: na

Solubility: Water Soluble

HAZARDOUS INGREDIENTS

Sand >50%

Cement >20%

Proprietary additives (non hazardous) <30%

Remaining products are not deemed to be hazardous and are commercially confidential.

HEALTH HAZARD & FIRST AID INFO

• SKIN CONTACT:

Prolonged exposure may cause skin irritation:
Wash off with water.

• EYE CONTACT:

May cause pain: Irrigate with water for at least 15 min.

• IF SWALLOWED:

Single dose oral toxicity is low BUT do not induce vomiting. DO call a doctor and transport to emergency facility for further instructions.

• IF INHALED:

Prolonged inhalation may cause irritation:
Ensure adequate ventilation.

• ENSURE SAFETY GLASSES ARE WORN FOR EYE PROTECTION

• GLOVES, BOOTS AND OVERALLS SHOULD BE WORN FOR PROLONGED CONTACT.

SPILLS: SMALL SPILLS: SHOULD BE MOPPED UP OR SOAKED UP . LARGE SPILLS: SHOULD BE CONTAINED. AVIOD SPILLAGE INTO WATER SUPPLIES.

CLEAN UP

Warm water clean –up prior to drying.