



Quikcote Victoria Plaster Technology Pty Ltd ABN 76 078 391 545  
26–30 Fleet Street Somerton, Victoria 3062  
Factory 9303 7791 Fax 9303 7792  
Email [info@quikcote.com.au](mailto:info@quikcote.com.au) Web [www.quikcote.com.au](http://www.quikcote.com.au)

**Quikcote Flexipatch** is a high polymer cementitious based, highly flexible acrylic render, giving superior strength.

**Quikcote Flexipatch** has been manufactured to give extreme strength, durability and long term weather resistance.

**Quikcote Flexipatch** can be used for many different applications due to its bonding strength and flexibility. Can be used to rejuvenate old and new surfaces.

**Quikcote Flexipatch** is suitable for:

- Masonary surfaces
- Rendered surfaces
- Cement sheet application.
- CSR \$ Hardies.
- Polystyrene Application
- Over painted surfaces, *provided paint substrate is stable, keep in mind that Flexipatch is bonding to the paint, not what the paint is bonded to.*

#### **SURFACE PREPARATION**

To ensure correct adhesion, surfaces must be suitably flat and clean ie: free of contaminants such as grease, waxes, paint and any oil based substances.

#### **APPLICATION**

A.A.C sheet recommended alkaline resistant mesh be used for jointing, giving added strength and will not rot like other bandages or mesh.

1. Apply a bedding coat into joints and let dry.
2. Apply armoring first coat to entire surface of project, finishing off with styrene or Perspex float.
3. Final coat to be applied on setting of the first coat, finish off with styrene float.
4. Use Quikcote Colorcote as a preferred finish or a suitable products to achieve desired look.

#### **COVERAGE**

On smooth surface :approx 5 -10 sq. metres.

#### **TECHNICAL DATA**

Specific Gravity: 1.86 kg/lt  
Odor: Nil  
Base: Cement  
Surface Finish: Medium  
Weather Resistance: High  
PH: 11  
Viscosity of Mix: (CPS) 95,000

#### **GUARANTEE:**

All products are guaranteed for seven years under \*normal conditions.

This product should be used in accordance with directions which are only a guide. Quikcote accepts no responsibility for inappropriate use or faulty workmanship. All mineral earth based aggregate /course filler based renders and textures will contain a low percentage of carbon and/or ferrous contaminants and can occasionally spot the surface. All care is taken in raw material selection to minimize such effects. Quikcote accepts no responsibility for this occasional occurrence.

#### **IDENTIFICATION**

Product Name: Flexipatch render  
UN Number: na  
Poisons Schedule Number: na  
Purpose: Surface Coating

#### **PHYSICAL DESCRIPTION**

Appearance: Off White  
Vapor Pressure: na  
Specific Gravity: 1.86 @ 25 Degrees Celsius  
Flammability: na  
Solubility: Water Soluble

#### **HAZARDOUS INGREDIENTS**

Sand >50%  
Cement >35%  
Proprietary additives (non hazardous) <15%  
***Remaining products are not deemed to be hazardous and are commercially confidential.***

#### **HEALTH HAZARD & FIRST AID INFO**

- **SKIN CONTACT:**

Prolonged exposure may cause skin irritation:  
Wash off with water.

- **EYE CONTACT:**

May cause pain: Irrigate with water for at least 15 min.

- **IF SWALLOWED:**

Single dose oral toxicity is low BUT do not induce vomiting. DO call a doctor and transport to emergency facility for further instructions.

- **IF INHALED:**

Prolonged inhalation may cause irritation:  
Ensure adequate ventilation.

- **ENSURE SAFETY GLASSES ARE WORN FOR EYE PROTECTION**

- **GLOVES, BOOTS AND OVERALLS SHOULD BE WORN FOR PROLONGED CONTACT.**

**SPILLS: SMALL SPILLS: SHOULD BE MOPPED UP OR SOAKED UP . LARGE SPILLS: SHOULD BE CONTAINED. AVIOD SPILLAGE INTO WATER SUPPLIES.**

#### **CLEAN UP**

Warm water clean –up prior to drying.